

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

State Well No.

10S/40E-1CC

State Permit No.

(1) OWNER:

Name Ray Saul
Address 3710 Grace St
Baker Ore 97814

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☒ Test Well ☐ Other ☐

CASING INSTALLED:

Threaded ☐ Welded ☒
8" Diam. from 0 ft. to 10.5 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? ☒ Yes ☐ No

Type of perforator used Torch
Size of perforations 1/8 in. by 6 in.
40 perforations from 80 ft. to 105 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is
lowered below static level

Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 22 gal./min. with 31 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used cement
Well sealed from land surface to 18 ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 13 sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons
of water lbs./100 gals.
Was a drive shoe used? ☒ Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Baker Driller's well number
SW 1/4 SW 1/4 Section 1 T.10S R. 40E W.M.

Bearing and distance from section or subdivision corner

250' N + 1000' E of SW Corner Sec 1

(11) WATER LEVEL: Completed well.

Depth at which water was first found 20 ft.

Static level 20 ft. below land surface. Date 11/2/77

Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing

Depth drilled 105 ft. Depth of completed well 105 ft.

Formation: Describe color, texture, grain size and structure of materials;
and show thickness and nature of each stratum and aquifer penetrated,
with at least one entry for each change of formation. Report each change in
position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top Soil	0	6	
Brown Clay	6	20	
Sand + Gravel	20	33	
Sand	33	37	
Sandy Blue Clay	37	70	
Light Blue Clay	70	90	
Gravel	90	105	

RECEIVED

JUN 18 1979

WATER RESOURCES DEPT.
SALEM, OREGON

Work started 10-19 1977 Completed 11-25 1977

Date well drilling machine moved off of well 11-26 1977

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision.
Materials used and information reported above are true to my
best knowledge and belief.

[Signed] Melvin L. Copley Date 12-1-77
(Drilling Machine Operator)

Drilling Machine Operator's License No. 671

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is
true to the best of my knowledge and belief.

Name Melvin L. Copley (Type or print)
(Person, firm or corporation)

Address Box 27 Sumpter Stage Baker Ore

[Signed] Melvin L. Copley
(Water Well Contractor)

Contractor's License No. 536 Date 12-1-77, 19